



C-915 Fifth Wheel Grease

Kendall® C-915 Fifth Wheel Grease is a smooth-textured calcium soap grease specially developed to handle the severe loads associated with fifth wheel applications.

C-915 Fifth Wheel Grease is manufactured with a heavy paraffinic base oil, a calcium stearate soap thickener and 10% graphite. It provides high load-carrying capacity for protection against wear, and is specially formulated to repel water and resist washout.

Applications

- Truck fifth wheels
- Mobile and industrial equipment operating at mild temperatures and under heavy loads

Features/Benefits

- High load-carrying capacity
- Excellent resistance to water washout

**Calcium Grease
With 10% Graphite
For Truck
Fifth Wheels**

U.S. Customer
Service:

1-800-368-7128

Technical Hot Line:

1-877-445-9198

International
Customer Service:

1-832-486-3363

1-832-486-3870

E-mail address:

**kendallmotoroil@
conocophillips.com**

C-915 Fifth Wheel Grease**Typical Properties**

NLGI Grade	1
Thickener	Calcium
Color	Black
Dropping Point, °C (°F)	141 (285)
Density, lbs/gal	7.52
Penetration, Worked (60 strokes), ASTM D217	310-340
Texture	Smooth/Tacky
Graphite, wt %	10
Base Oil Properties:	
Viscosity,	
cSt @ 40°C	434
cSt @ 100°C	29.2
SUS @ 100°F	2,320
SUS @ 210°F	144
Viscosity Index	95
Usable Temperature Range,	
°C	-9 to 46
°F	15 to 115

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2009 ConocoPhillips Company. ConocoPhillips, Kendall, their respective logos, the Two Finger logo, and Liquid Titanium are trademarks of the ConocoPhillips Company in the U.S.A. and other countries.