

March 9, 2012

P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNTHETIC HYDRAULIC

HYSYN FG SERIES

Summit HySyn FG Series hydraulic oils are formulated specially for hydraulic systems operating in the food service, beverage, and packaging industry. These fully synthetic lubricants are NSF Registered and meet USDA 1998 (H-1) guidelines (lubricants with incidental food contact). HySyn FG Series lubricants are Kosher/Halal certified and pending CFIA approval. Summit is an ISO 21469 certified facility.

HySyn FG lubricants are fortified with oxidation inhibitors, corrosion inhibitors, as well as anti-wear additives to enhance the superior qualities offered by the synthetic hydrocarbon base stock. They are extended life lubricants and have the same excellent software compatibility as the Summit HySyn Series hydraulic oils.

Physical Properties

HYSYN FG	FG-15	FG-22	FG-32	FG-46	FG-68	FG-100
ISO Grade	15	22	32	46	68	100
Viscosity						
@ 40°C, cSt	15.0	21.7	30.7	46.8	68.4	99.3
@ 100°C, cSt	3.58	4.56	5.80	7.79	10.4	13.9
@ 100°F, SUS	82	113	157	238	350	510
@ 210°F, SUS	38.3	41.6	45.7	52.3	61.5	74.9
Viscosity Index	122	127	134	135	139	141
Flash Point, °F (°C)	385 (196)	450 (232)	460 (238)	490 (254)	505 (263)	515 (268)
Fire Point, °F (°C)	440 (227)	495 (257)	525 (274)	565 (296)	565 (296)	585 (307)
Pour Point, °F (°C)	-103 (-75)	-94 (-70)	-81 (-63)	-71 (-57)	-65 (-54)	-60 (-51)
Emulsion Tendency	40/40/0 10 Mins	40/40/0 10 Mins	40/40/0 10 Mins	40/40/0 10 Mins	40/40/0 10 Mins	40/40/0 10 Mins
Specific Gravity	0.816	0.821	0.830	0.834	0.838	0.841
NSF Registered	H1	H1	H1	H1	H1	H1
ISO 21469	Yes	-	Yes	Yes	Yes	Yes
Kosher Approved	Yes	Yes	Yes	Yes	Yes	Yes
Halal Certified	Yes	Yes	Yes	Yes	Yes	Yes
CFIA Accepted	Yes	Pending	Yes	Yes	Yes	Yes

Percent By Weight Phosphorous 0.0695 Sulfur 0.047

HySyn FG-46 does not produce an iridescent appearance (sheen) on the surface of the water when tested in accordance with the U.S. Coast Guard Static Sheen Test.

Shelf Life: Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.