



## NS-MP Hypoid Gear Lubricant

Kendall® NS-MP Hypoid Gear Lubricant is a multipurpose, extreme-pressure, API GL-5 automotive gear lubricant specifically designed for use in passenger car and truck axles with hypoid gear sets.

NS-MP Hypoid Gear Lubricant is formulated to provide long service life and extended gear life in automotive differentials operating under varying conditions of speed, load, temperature and torque. The carefully balanced formulation is designed to minimize oxidative sludge and varnish formation, reduce wear, prevent scoring damage, and protect against metal fatigue and spalling damage under shock-load conditions.

### **Applications**

- Service fill of conventional differentials on passenger cars and trucks
- Top-off only of limited-slip differentials on passenger cars and light trucks<sup>(1)</sup>
- Service fill of differentials, final drives and transfer cases in some off-highway equipment
- Non-synchronized manual transmissions in trucks, buses and heavy equipment where the manufacturer specifies an API GL-5 or MT-1 gear oil

<sup>(1)</sup> **Note:** For complete drain and refill, many limited-slip differentials may require the manufacturer's specified gear lubricant or supplemental additive. Refer to the owner's manual for specific requirements.

NS-MP Hypoid Gear Lubricant meets or exceeds the requirements of:

- API Service GL-5, MT-1
- ArvinMeritor O76-A (SAE 85W-140), O76-D (SAE 80W-90), O76-E (SAE 75W-90)
- Ford WSP-M2C197-A (SAE 80W-90)
- Mack GO-J
- MIL-PRF-2105E
- SAE J2360

### **Features/Benefits**

- Excellent oxidation resistance and thermal stability to minimize sludge and varnish formation
- Excellent thermal durability and extreme-pressure (EP) properties for extended gear life

**Multipurpose  
Automotive  
Gear Lubricant,  
API GL-5/MT-1**

U.S. Customer  
Service:

**1-800-368-7128**

Technical Hot Line:

**1-877-445-9198**

International  
Customer Service:

**1-832-486-3363**

**1-832-486-3870**

E-mail address:

**kendallmotoroil@  
conocophillips.com**

- High load-carrying capacity for protection against scuffing and wear
- Protects against rust and corrosion
- Good foam resistance

### NS-MP Hypoid Gear Lubricant

#### Typical Properties

SAE Grade	75W-90	80W-90	85W-140
Specific Gravity @ 60°F	0.878	0.887	0.896
Density, lbs/gal @ 60°F	7.32	7.38	7.46
Color, ASTM D1500	1.5	3.0	4.0
Flash Point (COC), °C (°F)	188 (370)	212 (417)	216 (421)
Pour Point, °C (°F)	-42 (-44)	-30 (-22)	-18 (0)
Viscosity, Brookfield			
cP @ -40°C	146,500	—	—
cP @ -26°C	—	114,000	—
cP @ -12°C	—	—	61,500
Viscosity, Kinematic			
cSt @ 40°C	102	140	319
cSt @ 100°C	14.6	14.0	24.7
Viscosity Index	149	99	97

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2009 ConocoPhillips Company. ConocoPhillips, Kendall, their respective logos, the Two Finger logo, and Liquid Titanium are trademarks of the ConocoPhillips Company in the U.S.A. and other countries.