



SHP® Synthetic Transoil 50

Kendall® SHP Synthetic Transoil 50 is a full-synthetic, SAE 50 transmission lubricant designed for use in heavy-duty manual transmissions in trucks and buses operating in extreme temperatures and/or extended service intervals. It combines improved low-temperature properties with outstanding oxidation resistance and thermal stability at high temperatures to provide excellent all-weather, year-round performance.

SHP Synthetic Transoil 50 has excellent shear stability and antiwear properties to protect synchronizers, reduce component wear and promote longer transmission life. It is particularly recommended for use in newer, higher torque manual transmissions coupled with increased horsepower engines. It meets the requirements of the Eaton PS-164 Rev 7 specification, and is fully approved for extended drain service (500,000 miles in line-haul service) in Eaton Roadranger® and Dana transmissions.

Applications

- Heavy-duty truck and bus manual transmissions where the OEM specifies a non-EP gear oil (API GL-1/MT-1) or SAE 50 heavy-duty engine oil

SHP Synthetic Transoil 50 meets or exceeds the requirements of:

- API Service GL-1, MT-1
- ArvinMeritor O-81
- Dana Spicer transmissions
- Eaton Fuller transmissions
- Eaton Roadranger® PS-164 Rev 7
- International TMS 6816
- Mack TO-A Plus
- ZF Freedomline transmissions

Features/Benefits

- Extended drain, all-season performance
- Outstanding oxidation resistance and thermal stability to minimize sludge and varnish formation
- Excellent low-temperature properties for easier shifting in cold weather
- High shear stability
- High load-carrying capacity
- Protects against component wear and gear micropitting
- Protects against rust and corrosion
- Good foam resistance

**Premium
Full-Synthetic
SAE 50 Manual
Transmission Fluid,
API GL-1/MT-1**

U.S. Customer
Service:

1-800-368-7128

Technical Hot Line:

1-877-445-9198

International
Customer Service:

1-832-486-3363

1-832-486-3870

E-mail address:

**kendallmotoroil@
conocophillips.com**

www.conocophillips.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



- Excellent seal compatibility
- Potential fuel economy benefits compared with non-synthetic transmission fluids

SHP® Synthetic Transoil 50

Typical Properties

SAE Grade	50
Specific Gravity @ 60°F	0.860
Density, lbs/gal @ 60°F	7.16
Color, Visual	Amber
Flash Point (COC), °C (°F)	221 (430)
Pour Point, °C (°F)	-45 (-49)
Viscosity, Brookfield	
cP @ -40°C (Brookfield)	104,000
Viscosity, Kinematic	
cSt @ 40°C	132
cSt @ 100°C	17.5
Viscosity Index	146

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2009 ConocoPhillips Company. ConocoPhillips, Kendall, their respective logos, the Two Finger logo, and Liquid Titanium are trademarks of the ConocoPhillips Company in the U.S.A. and other countries.