

Tier One Lubricants™ Multi-purpose Automatic Transmission Fluid

Product Description

Tier One LubricantsTM Multi-purpose Automatic Transmission Fluid is a multi-purpose product for use in GM and Ford automatic transmissions. It is formulated to meet the viscometrics, friction, wear and oxidation stability properties required in passenger car and light truck transmissions.

Industry and OEM Specifications

- *Allison C-4, C-3 (C30502004)
- *GM Dexron® III/II (Obsolete)
- *Ford Mercon® (Obsolete)
- *Caterpillar TO-2
- *Voith G607
- *Volvo S6/66 manual transmission

Applications

Tier One LubricantsTM Multi-purpose Automatic Transmission Fluid is recommended for use in GM and Ford automatic transmissions except for those that specify GM Dexron® VI, Ford Mercon® V, and Ford Type F. Due to Voith, ZF approvals it is an excellent choice for bus fleets. This fluid can also be used as power steering fluid for most US manufactured cars.

Typical Properties

| | Test | D/M | |
|--------------------|--------|-----|--|
| Viscosity at 100°C | D445 | 7.1 | |
| Viscosity Index | D2770 | 191 | |
| Pour Point ° C | D97 | -40 | |
| Color | Visual | Red | |

The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. All of them may vary within modest ranges.