



**TIER ONE**  
LUBRICANTS  
PRODUCT DATA SHEET

## Tier One Lubricants™ NGE0 Ashless

### Product Description

Tier One Lubricants™ NGE0 Ashless engine oils are formulated for two-cycle and four-cycle stationary natural gas and LP fueled engines. These oils provide excellent control of deposits, wear, oil oxidation and oil nitration in naturally aspirated engines.

### Industry and OEM Specifications

- Ajax
- Allis-Chalmers
- Caterpillar (except 6400, 3500, 3600)
- Clark
- Climax
- Colt-Fairbanks Morse
- Copper Bessemer (2 Cycle)
- Dresser-Rand Category I and II
- International Harvester
- Waukesha
- White Superior naturally aspirated
- Worthington (2 Cycle)

### Applications

Tier One Lubricants™ NGE0 Ashless engine oil is recommended for natural gas-fueled engines used in gas transmission and compression, total energy plants, electric power generation and irrigation pumping service.

### Typical Properties\*

SAE GRADE	Test	SAE 30	SAE 40
Viscosity @ 100°C	D445	10.4	14.3
Viscosity Index	D2770	95	95
Pour Point °C	D97	-20	-20
TBN	D2896	5.1	5.1
Sulfated Ash mass%	D874	0	0
Flash Point, COC, °C	D92	240	265

\*The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. All of them may vary within modest ranges.