



TIER ONE
LUBRICANTS
PRODUCT DATA SHEET

Tier One Lubricants™ Tractor Hydraulic Fluid

Product Description

Tier One Lubricants™ Universal Tractor Hydraulic Fluid (UTHF) is an all season hydraulic and transmission fluid designed to meet the special lube requirements of most tractors and implements. It is formulated to provide extreme pressure (EP) protection, resist oxidation and corrosion, and disperse moisture.

Industry and OEM Specifications

- * AGCO-ALLIS, ALLIS-CHALMERS (Deutz-Allis) Powerfluid 821XL, PF821, 272843, 257541, 2466
- * Allison C-4, C-3
- * Case JIC-143, 144, 145, 185, MS-1210/1209/1207/1206/1205/1204
- * Caterpillar TO2
- * Clark Transmissions MS266 (lift truck)
- * Dennison HF-0, HF-1, HF-2
- * Heston-Fiat AF-87
- * John Deere J20C/20A/20B/14B/C, JD 303
- * Ford New Holland M2C134-A/B/C/D, M2C53-B, M2C48-B, M2C86-B, FNHA-2-C-200/201, ESN-M2C41-B
- * Kubota UDT
- * International Harvester IHC B-6/B-5 (HY-Tran)
- * Landini (M1135)
- * Massey Ferguson M1141 (Permatran III), M1135, M1129A, M1127 A/B
- * Minneapolis-Moline 35154/35202/35301
- * Oliver Type 55 & S3727B Fluid
- * Renk 874 A/B Transmission
- * Steiger SEMS 17001
- * Vickers M-2950-S, I-286-S
- * White Farm Q-1286/1705/1766B/1802 (Type 55)

Typical Properties*

	Test	15W20
Viscosity at 100°C	D445	9.2
Color	D1500	L2.5
Pour Point °C	D97	-35

*The values shown here are representative of current production. Some are controlled by manufacturing specifications while others are not. All of them may vary within modest ranges.