

**CITGO TRANSGARD® TRACTOR
HYDRAULIC FLUIDS**

Date 01/10

- DESCRIPTION:** These products are multifunctional tractor hydraulic/transmission fluids which perform the following functions:
- Lubricate the transmission, differential and final drive gears.
 - Act as a power steering, power brake, power take-off and implement drive fluid.
 - Provide a medium with the correct friction and heat transfer characteristics for proper operation of the tractor wet brakes and power take-off unit.
- CITGO TRANSGARD Lo-Temp Tractor Hydraulic Fluid is specially designed to provide outstanding low temperature fluidity under the coldest conditions. It has the same performance benefits as TRANSGARD Tractor Hydraulic Fluid, but is intended for applications where a lower viscosity fluid is desired.
- QUALITIES:** The following characteristics make CITGO TRANSGARD Tractor Hydraulic Fluids outstanding products for multi-functional application.
- Superior extreme pressure (EP) and antiwear performance protects tractor transmissions, axles and hydraulic pumps. The frictional characteristics are designed to minimize "chatter" while permitting the wet brakes to hold properly. This frictional balance also provides smooth engagement of the power take-off clutch.
 - Special blend of base stocks helps maintain seals and gaskets.
 - Balanced formulations provide excellent rust and corrosion protection as well as excellent oil oxidation stability for high-temperature service.
 - Is approved by Denison Hydraulics as an HF-0 quality fluid.

(Continued)

CITGO TRANSGARD® TRACTOR
HYDRAULIC FLUIDS



Date 01/10 - (Continued)

- APPLICATIONS:** CITGO TRANSGARD® Tractor Hydraulic Fluid is intended for most hydraulic fluid and transmission oil applications for tractors and implements where the following are recommended:
- | | |
|---|--|
| Agco-Allis | KOMATSU/Dresser |
| Allis Chalmers PF 821XL | KUBOTA Universal Transdraulic Fluid (UDT & Super UDT) |
| Allison (ATD) C-3 | Massey Ferguson M1110, M1127 B, M1129 A, M1135 (European Spec.), M1141 (Permatran® III) |
| Belarus | McCormick Farmall |
| David Brown | Minneapolis-Moline |
| Case New Holland (CNH) MS-1204; MS-1205 (TFD II); MS-1206 (Powergard® PTF); MS-1207 (HyTran® Plus); MS-1209; MS-1210 (TCH) and B-6; (JIC-144); (JIC-145); TFD (JIC-143 & 146); Hi-Vis (JIC-185) | Mitsubishi |
| Caterpillar TO-2 | New Idea |
| John Deere Quatrol®; J20 A, J20 C, ⁽¹⁾ Hy-Gard® J14 B/C, Type 303 | Oliver Type 55 |
| Duetz-Allis HTF (PF821); 821 XL | Renk-Doromat 873 or 874 A/B Bus Transmissions (unmodified units only) |
| Ford New Holland M2C134-A/B/C/D, M2C86-B/C (European Spec.), (M2C41-B) (M2C48-A/B), (M2C53-A/B) (M2C43) (M2C92-A) | Steiger HTF (SEMS 17001) |
| Hesston and Hesston Fiat AF-8T | Universal |
| IMT | Valmet |
| International Harvester B-6 (Hy-Tran®) | Volvo WB-101 |
| International Hough (Dresser) | Versatile Hy-Gear (23M, 24M) |
| KIOTA | White Farm Equipment Q1705, Q1722, Q1766B (UHTF), Q1802, Q1826 |
| KOMATSU | Hydraulic System Mfgs: Denison HF-0, HF-1, HF-2, Eaton Hydraulics; Vickers I-2986-S, M-2950-S; Sauer-Sunstrand Hydraulics |

Note: (1) Meets the performance requirements of Allison C-4 as specified by John Deere.

CITGO TRANSGARD Lo-Temp Tractor Hydraulic Fluid is intended for winter operating conditions (down to -40°F), or where a hydraulic/transmission lubricant with improved low temperature properties is desired. It has been formulated to meet the John Deere J20D specification.

TYPICAL PROPERTIES:

CITGO TRANSGARD® TRACTOR HYDRAULIC FLUID

	TRACTOR HYDRAULIC FLUID	LOW-TEMP TRACTOR HYDRAULIC FLUID
Material Code	633310001	633311001
Gravity, ASTM D 4052, °API	29.7	32.3
Density, lb/gal	7.30	7.20
Flash Point, COC, ASTM D 92, °F (°C)	450 (232)	406 (208)
Viscosity, ASTM D 2983, cP at	-4°F (-20°C)	5,500
	at -29°F (-35°C)	48,200
	at -40°F (-40°C)	-
ASTM D 445, cSt at 40°C	60.3	15,300
cSt at 100°C	9.3	33.7
Viscosity Index, ASTM D 2270	130	7.15
Pour Point, ASTM D 97, °F (°C)	-40 (-40)	183
Color, ASTM D 1500	3.0	-54 (-48)
Foam Test, ASTM D 892, Sequence 1, II, III	Pass	2.5
		Pass